TOSHIBA
Leading Innovation >>>

e·STUDIO408P
e·STUDIO478P

Product brochure

> Reliable A4 monochrome printers to boost the efficiency of small and medium sized businesses or workgroups.

> High quality printing on a broad range of media at speeds of up to 40/47 pages per minute respectively.

> Designed to meet the highest environmental standards, the printers have a low energy consumption, helping save money and resources.

TOGETHER INFORMATION

READY WHEN YOU ARE

For day-to-day business, you need a printer you can rely on, which delivers impeccable document output every time you print. Toshiba's e-STUDIO408P and e-STUDIO478P offer just that. With a print speed of 40 and 47 pages per minute (ppm) respectively and a fast first print output time, these productive printers are ready when you need them.

Compatible with most operating systems the printers are easy to install and even easier to use. Thanks to their network capability and their mobile printing features the e-STUDIO408P and e-STUDIO478P are ideal for small- and medium-sized businesses and workgroups. And if needed, they can grow with your needs, e.g. by adding additional paper sources to increase the capacity. For more advanced functionality the e-STUDIO478P comes with a large range of further options, which will enhance your efficiency even more.

High-level security features are of course standard for the e-STUDIO408P and e-STUDIO478P and protect the devices from unauthorised access.

CONFIGURATION

e-STUDIO408P

e-STUDIO478P

250-sheet Drawer
KD-1060

550-sheet Drawer
KD-1061

Swivel Cabinet
MH-3100

Adjustable Printer Stand
KK-3200

SPECIFICATIONS

General

Print Speed	40 ppm
Warm-up Time	Approx. 9 seconds (from sleep mode)
Paper Size & Weight	A6-A4/custom, 60-120 gsm (Cassette) 76x127 mm - 216x356 mm, 60-216 gsm (Bypass)
Paper Capacity	1x 250 sheets (Cassette), 1x 100 sheets (Bypass) Maximum 900 sheets
Inner Output Tray	150-sheet capacity
Automatic Duplex	A4/custom, 60-90 gsm
Control Panel	2 line OLED display
Memory	Standard: 512 MB, Maximum: 512 MB
Interface	10Base-T/100Base-TX/1000Base-T (incl. IPv6), High Speed USB 2.0
Dimensions & Weight	399 x 374 x 260 mm (W x D x H), ~ 14 kg
Starter Kit	Starter cartridge with Toner and Imaging unit

Print

Resolution	Maximum 1,200 x 1,200 dpi
First Print Output Time	Approx. 6 seconds
Page Description Language	PCL 6, PCL 5, PostScript 3 and PDF v1.7 emulation, XPS, PPDS
Supported Systems	Windows 10/8/8.1/7, Windows Server 2016/ Server 2012/Server 2008 (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64bit), Mac OS X 10.6-10.11, Linux/Unix, Novell NetWare, Citrix, SAP
Mobile Printing	AirPrint, Mopria Print Service, Google Cloud Print
Print Functions	Universal Printer Driver, Multiple pages per sheet, Envelope printing

System & Security

Device Management	e-BRIDGE Fleet Management System[1]
System Features	Energy saving modes, Automatic toner saturation/ darkness adjustment
Accounting & Security	Private print, IP address filter, Port filter, Support of SNMPv3, Operator Panel Lock

Options

250-sheet Drawer	250-sheet capacity, A5-A4, 60-120 gsm
550-sheet Drawer	550-sheet capacity, A5-A4, 60-120 gsm
Swivel Cabinet	
Adjustable Printer Stand	
User Flash Memory	
Forms and Barcode Card	

[1] Optional

e-STUDIO408p
standard configuration

e-STUDIO408p
w/ 550-sheet Drawer

e-STUDIO478p
w/ 2x 550-sheet Drawer

e-STUDIO478p
w/ 3x 550-sheet Drawer

SPECIFICATIONS

e-STUDIO478P

General

Print Speed	47 ppm
Warm-up Time	Approx. 9 seconds (from sleep mode)
Paper Size & Weight	A6-A4/custom, 60-120 gsm (Cassette) 76x127 mm - 216x356 mm, 60-216 gsm (Bypass)
Paper Capacity	1x 550 sheets (Cassette), 1x 100 sheets (Bypass) Maximum 2,300 sheets
Inner Output Tray	250-sheet capacity
Automatic Duplex	A4/custom, 60-90 gsm
Control Panel	6 cm (2.4") Colour LCD panel
Memory	Standard: 512 MB, Maximum: 512 MB
Interface	10Base-T/100Base-TX/1000Base-T (incl. IPv6), High Speed USB 2.0, WLAN[1] (IEEE802.11 ac/a/b/g/n 2x2 MIMO Wireless)
Dimensions & Weight	399 x 374 x 303 mm (W x D x H), ~ 15.8 kg
Starter Kit	Starter cartridge with Toner and Imaging unit

Print

Resolution	Maximum 1,200 x 1,200 dpi
First Print Output Time	Approx. 6 seconds
Page Description Language	PCL 6, PCL 5, PostScript 3 and PDF v1.7 emulation, XPS, PPDS
Supported Systems	Windows 10/8/8.1/7, Windows Server 2016/ Server 2012/Server 2008 (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64bit), Mac OS X 10.6-10.11, Linux/Unix, Novell NetWare, Citrix, SAP
Mobile Printing	AirPrint, Mopria Print Service, Google Cloud Print
Print Functions	Universal Printer Driver, Multiple pages per sheet, Envelope printing

System & Security

Device Management	e-BRIDGE Fleet Management System[1]
System Features	Energy saving modes, Automatic toner saturation/ darkness adjustment
Accounting & Security	Private print, IP address filter, Port filter, Support of SNMPv3, SSL and IPsec protocols, 802.1x authentication[1], Operator Panel Lock

Options

250-sheet Drawer	250-sheet capacity, A5-A4, 60-120 gsm
550-sheet Drawer	550-sheet capacity, A5-A4, 60-120 gsm
Swivel Cabinet	
Adjustable Printer Stand	
User Flash Memory	
Wireless LAN Module	
Forms and Barcode Card	
PRESCRIBE Card	
IPDS Card	

[1] Optional

ENERGY STAR